THE TINOVO PORTFOLIO

Products & *specifications.*

Prime imported steel across five product lines, every consignment supplied with mill test certificates.

TINPLATE TFS STEEL PIPE GI CR PPGI

01 / THE RANGE

Tinplate & TFS



TINPLATE · ILLUSTRATIVE



TFS / ECCS · ILLUSTRATIVE

Electrolytic tinplate and tin-free steel (TFS/ECCS) for food and beverage cans, aerosols, paint containers, crown corks and closures, in prime, assorted and secondary parcels from Japan, Korea, Taiwan and Europe.

Thickness	0.13 – 0.49 mm
Form	Coils & sheets (scroll / straight cut)
Tin coating	1.1 – 11.2 g/m² (E1 to E4; differential available)
Temper	T1 – T5, DR7 – DR9

Standards	JIS G3303, EN 10202, ASTM A623

ENQUIRE ABOUT THIS PRODUCT ↗

02 / THE RANGE

Steel Pipe & Tube



ILLUSTRATIVE IMAGE

ERW black, galvanized and precision pipe and tube imported from Korea, Taiwan and China for structural, general engineering, scaffolding, water and gas line applications.

Outside diameter	15 NB – 300 NB (21.3 – 323.9 mm)
Wall thickness	1.6 – 12.7 mm
Length	5.8 / 6.0 / 11.8 / 12.0 m & cut-to-length
Finish	Black, hot-dip galvanized, pre-galvanized
Standards	ASTM A53, ASTM A500, BS 1387, EN 10219, JIS G3444, IS 1239

ENQUIRE ABOUT THIS PRODUCT ↗

03 / THE RANGE

GI Coils & Sheets



ILLUSTRATIVE IMAGE

Hot-dip galvanized steel for ducting, panels, purlins, drums, appliances and general fabrication, sourced from mills in Korea, Taiwan and China.

Thickness	0.13 – 3.0 mm
Width	750 – 1,500 mm (slit widths available)
Zinc coating	Z60 – Z275 g/m²
Spangle	Regular, minimized, zero
Standards	ASTM A653, EN 10346, JIS G3302, IS 277

ENQUIRE ABOUT THIS PRODUCT ↗

04 / THE RANGE

CR Coils & Sheets



ILLUSTRATIVE IMAGE

Full-hard and batch/continuously annealed CR for automotive ancillaries, appliances, furniture, drums and precision tubing, with surface-critical grades from Japanese and Korean mills.

Thickness	0.12 – 3.0 mm
Width	600 – 1,550 mm
Temper	Full hard, annealed (soft), ¼ / ½ / ¾ hard
Grades	CQ, DQ, DDQ, EDDQ
Standards	JIS G3141 (SPCC/SPCD/SPCE), EN 10130 (DC01–DC04), ASTM A1008, IS 513

ENQUIRE ABOUT THIS PRODUCT ↗

05 / THE RANGE

PPGI



ILLUSTRATIVE IMAGE

Colour-coated coils for roofing and wall cladding, sandwich panels, appliances and furniture, in standard and custom RAL shades with guard film on request.

Thickness (TCT)	0.18 – 1.2 mm
Width	900 – 1,250 mm
Paint system	RMP / SMP / PVDF; 15–25 µm top, 5–7 µm back
Substrate	GI (Z60–Z180) or Galvalume (AZ70–AZ150)
Colours	Full RAL range; matt & wrinkle finishes
Standards	EN 10169, ASTM A755, JIS G3312

ENQUIRE ABOUT THIS PRODUCT ↗

All ranges indicative, confirm per enquiry.